



THREATS



NIJ 0101.06

TETRA

LEVEL II | SOFT BODY ARMOR

- AD** AREAL DENSITY: **0.89 psf**
- T** THICKNESS: **0.21"**
- F** FLEXIBILITY: **Medium**
- S** TEMPLATE SIZES: NIJ C-1 through NIJ C-5
- PA** PRODUCT APPLICATION:
Concealable Body Armor, External Carriers,
Plate Carriers, and Tactical Body armor
- M** TYPE OF MATERIALS:
500D Twaron® Plain Weave
Twaron® 4-Ply Unidirectional Fabric
- C** TYPE OF CONSTRUCTION:
W.R.A.P.™ — Water Repellent Armor
Perimeter (Patent Pending)
- PC** TYPE OF PROTECTIVE COVER:
Brookwood 70D with Laminated Polyurethane
- PS** TYPE OF PROTECTIVE SEAL:
Sonobond Ultrasonic Bond
- SG** AVAILABLE SHAPES AND GRADES:
Available in ALL vest patterns as well as OEM
Armor Specifications
- ST** SPECIAL THREAT TESTING*:
9mm V50: 1699 fps
.357 Mag V50: 1632 fps
FN SS197 40 grain V0
Win SXT 9mm +P+ V0
7.62x25 Tokarev 85 grain V0
.357 SIG Win SXT 125 grain V0
Corbon 9mm +P 90 grain V0

*Special Threat Testing Conducted in accordance with an abbreviated and modified NIJ 0101.06 and AFCI Special Threat Testing Protocol.

